

The MAXHUB UC S10 Unified Communication Bar

UNLEASH THE POWER
OF COLLABORATION
WITH THE MAXHUB UC S10

Superior imagery and pro audio ensure you see every face and hear every word. Built-in Android provides effortless connection. Easy setup and operation remove every barrier to successful meetings.

Collaborate Effortlessly

Wireless screen-sharing | Parallel Wi-Fi networking

A meeting communication hub, the UC S10 enables you to share ideas, images and data with ease and keeps the meeting flowing.





A Visionary Camera

Auto-framing | 3 Camera position presets | 120° Viewing angle | 12MP | 5X digital zoom









> FOCUSES ON THE PRESENTER

Auto-framing with intelligent face detection tracks whoever is speaking and smoothly switches between presenters.

3 CAMERA POSITION PRESETS

Enable instant meeting start up, free from repeated camera setting

) 120° FOV

Full room coverage

MAXHUB

Studio-quality Sound

6-element Microphone | 8W Speakerphone



Adaptive echo canceller



Automatic tracking



Noise reduction



Automatic gain control



Dereverberation

HD Voice Noise

Start Simply

From initial installation to setup and everyday operation, MAXHUB UC S10 embodies simplicity and maximizes meeting efficiency.



5-in-1 compact design

Next-generation camera, speakerphone, microphone, screen-share and Android are built in.

> Flexible installation

Designed for table stand, TV or wall mounting without the need for special construction.

1-minute simple setup

With built-in Android, there's no computer needed.

Simply start a teleconference with the app you prefer, either from a computer or from the UC S10. Connect it to the display, and you're ready to go.

Specification

* Specifications are subject to change without notice.

Specification	
Camera	
Sensor	1/2.3 inch CMOS, 12MP
Scanning Mode	Progressive
Filed of View (DFOV)	120°
Tilt Range	Up 15°, Down 15°
Focal Length	Fixed
Frame Rate	4K@30fps
Minimal Focusing Illumination	0.05 Lux (@f/2.4, AGC On)
White Balance	Auto
Digital Noise Reduction	2D& 3D Digital Noise Reduction
Backlight Compensation	Yes
Camera Mount	Magnet+ M12
Features	EPTZ, Auto-framing
Sound	
Maximum Sound Pressure Level (dBSPL)	86dBSPL@1m, 1kHz
Frequency Range (-10dB)	150Hz~15kHz
Total Harmonic Distortion	≤5%
Signal to Noise Ratio	≥75dB
Speaker Channel	1
Output Power	1×8W
Microphone	
Number of Microphones	6
Microphone Type	MEMS
Pickup Range	8 Metres
Frequency Response	100Hz~7.5kHz
Pickup Angle	180° front
Features	Noise Reduction, Echo Cancellation,
	Beamforming, Voice Localisation
Power	
Input Voltage	12V
Power Consumption (Typ.)	36W
Current Consumption	3A
Package Contents	
UC-S10 Video Bar	x1
HDMI Cable	×1 (1.5m)
Remote Control	×1
Battery	×2 (AAA)
Power Adapter	×1
Wall-mounted Components	×1
Lens Cover	×1
USB Cable	×1 (3m)
Quick Guide	×1

USB Features	
Operating System	Windows 7 (Up to 1080P), Windows 8.1, Windows 10
Hardware Requirement	2.4GHz Intel Core 2 Duo Processor or above
	2GB RAM or above
Colour System/Compression	H.264/YUY2/MJPG
Video Format	4K@30fps/25fps, 1080P@30fps/25fps, 720P@30fps/25fps,
	960 × 540P@30fps/25fps, 640 × 360P@30fps/25fps, etc
USB	USB 2.0
USB Audio	Build-in Mic and Speaker
UVC	1.1
USB Host	USB 3.0
Input/Output Interface	
LINE IN/OUT	1×3.5mm earphone port
HDMI OUT	1×HDMI 1.4
Internet Connection	Ethernet: 1×RJ45(10/100Mbps), Wi-Fi: 2.4G/5G Dual Band Wi-Fi
	1×USB 2.0: Type C, Device
USB Interface	1×USB 3.0: Type A, Host
DC In	1×DC 2.0
RJ45	1x (10/100mbps)
Built-in System	
Processor	2x A73 + 2x A53
Memmory	4GB
Storage	16GB
Audio DSP	ARM 4x A35
Operating System	Android 8.0
System Feature	Wireless Screenshare, Wireless dongle (optional)
Environment Requirement	
Operation Temperature	0°C - 40°C
Operation Humidity	10% - 90%RH
Storage Temperature	-20°C - 60°C
Storage Humidity	10% - 90%RH
Physical Specification	
Dimension L×H×D	462×76×93 mm
Dimension (package) L × W × H	540×160×170 mm
Net Weight	1.026KG
Gross Weight	2.330KG
Warranty	
Camera	3 years
Accessories	1 year
Compatible Application	
Support Major VC Software	ZOOM, Microsoft® Teams, Google Meet,
	Google Hangouts, Cisco WebEx®, RingCentral, etc.







